

SPC Flooring

Product Catalog



Product Specification

- Thickness - 4.0 mm
- Wear layer - 0.3 mm
- Interlocking system (tongue and groove)
- Plank Size - 7" X 48" (177.8 mm X 1219.2 mm)
- Area of 2.33 sq.ft per plank
- Surface treatment – UV coating



Product Characteristics

- Superior antiskid
- Antimildew and antibacterial
- Comfortable to walk on
- Lightweight
- Waterproof and damp proof
- Environmentally-friendly and renewable
- Fire retardant
- Sound absorption and noise reduction



Technical Data Sheet

Characteristics	Standards	Result
Residual Indentation	EN 434	0.09mm
Dimensional stability	EN 434	0.03%(80°C,6hrs)
Curling	EN 434	≤1.2mm(80°C,6hrs)
Flexibility	EN 435	Pass
Determination of migration of heavy metals	US EPA 3025:1996	None
Phthalate content & Lead content	CA65	Pass
Substances of Very High Concern(SVHC)	SGS In-House method	Pass
Flammability	EN 13501-1	Class Bf1
Formaldehyde emission	EN 717-1	Class E1
Slip resistance	EN 13893	Class DS
Abrasion resistance	EN 660-2	Group T
Castor wheel test	EN425	Pass
Color fastness	EN ISO 105-B02	≥6
Peel resistance	EN 431	≥2.8Kgf/cm ²
Sound reduction	EN ISO 10140	9dB



Ashwood



Burma Teak

The image features a dark brown wood grain texture as a background. A white diamond shape is centered on the left side, outlined with a thin white border. Inside the diamond, the words "Dark Oak" are written in a black, elegant cursive font.

Dark Oak



Hazelwood

The image features a background of light-colored wood with a vertical grain pattern. A white diamond shape is centered on the left side of the image. Inside this diamond, the text "Light Walnut" is written in a black, elegant cursive font.

Light Walnut

The image features a dark wood-grain background with a white diamond shape in the center. The word "Ebony" is written in a black, elegant cursive font within the white diamond. The diamond is outlined by a thin, light-colored border.

Ebony

Contact Us



No 102, Havelock road,
Colombo 05.



+ (94) 77 238 4629



projects@globalvinyl.lk



www.globalvinyl.lk

