



Luxury Vinyl Tile - LVT

TECHNICAL DATA SHEET

Characteristics	Standards	Specification	
Total Thickness	EN ISO 24346	2.00 mm	3.00 mm
Wear Layer Thickness	EN ISO 24340	0.50 mm	0.50 mm
Dimension of Plank	EN ISO 24342	6" x 36" 152.4mm X 914.4mm	6" x 36" 152.4mm X 914.4mm
Weight of Plank	g/sq.ft	300	450
Gloss Value (Matt)	ISO 2813:2014	5	5
Dimensional Stability	ASTM F2199	Pass	Pass
Pass Hardness Shore D	ISO 7619:2010	>55	>55
Abrasion Resistance	EN 660-2	Group T	Group T
Resistance to Chemicals	EN ISO 26987	1	1
Reaction to Fire	EN ISO 11925-2	Class Bf1-s1	Class Bf1-s1
Castor Chair Test	ISO 4918	OK	OK
Thermal Conductivity	EN ISO 10456	0.25 W/(m.K)	0.25 W/(m.K)

© LUCKY DISSANAYAKE GRAPHICS | 0177-942-537

LVT or Luxury Vinyl Tile is an innovative design of vinyl flooring. An affordable alternative to wood or stone. The realistic look of either wood, stone or ceramic tile is extremely hard wearing and resilient to daily wear and tear. It has a scratch resistant surface and waterproof making it ideal for any room in your home. The LVT is made up of multiple thin layers so that the flooring is still flexible but very durable and easy to look after.



Hotline (+94) 77 298 4212