

Luxury Vinyl Tile - LVT

TECHNICAL DATA SHEET

Characteristics	Test Method	Test Results
Type of Flooring	ISO 10582:2017	Resilient Flooring
Thickness	ISO 24346:2006	2.00 mm / 3.00 mm
Wear Layer Thickness	ISO 24340:2006	0.30 / 0.50 / 0.70 mm
Dimension of Plank	ISO 24342:2018	152.4mm X 914.4mm (6" X 36") 177.8mm X 1219.2mm (7" X 48")
Weight	ISO 23997:2012	3800 gsm / 5810 gsm
Abrasion Resistance	ISO 10582:2017	Group T; Type 1
Dimension Stability	ISO 23999:2021	≤ 0.20mm
Residual Indentation	ISO 24343-1:2007	≤ 0.10mm
Flexibility	ISO 24344:2008	No Cracks (20mm Mandrel)
Colour Fastness	ISO 105-B02:2014	Grade 6
Slip Resistance	DIN 51130:2014	R9
Castor chair test	ISO 4918:2016	After 25,000 cycles: Delamination - None
Reaction to Fire	EN 13501-1	Bfl-s1
Surface Treatment		UV Coating
Emboss Pattern		Wood & Classic
Installation Method		Glue down

LVT or Luxury Vinyl Tile is an innovative design of vinyl flooring. An affordable alternative to wood or stone. The realistic look of either wood, stone or ceramic tile is extremely hard wearing and resilient to daily wear and tear. It has a scratch resistant surface and waterproof making it ideal for any room in your home. The LVT is made up of multiple thin layers so that the flooring is still flexible but very durable and easy to look after.



Hotline (+94) 77 238 4625